


# ipso 040

**Drosselrückschlagventil mit Steckverschraubung und Rändelkopf, Typ B, Abluft drosselbar**

**Flow regulator with push-in fittings and handwheel regulator type B**

**Regolatore di flusso manuale unidirezionale per cilindri tipo B**



| ITV    | ØD | G    | H | ØB | L1 max | L2   | sw | NI/min* |
|--------|----|------|---|----|--------|------|----|---------|
| 204003 | 8  | G1/8 | 5 | 14 | 49     | 24,5 | 14 | 340     |

|                                 |                         |
|---------------------------------|-------------------------|
| Körper:                         | CW617N vernickelt       |
| Body:                           | CW617N nickel-plated    |
| Corpo:                          | ottone CW617N nichelato |
| O-Ring:                         | NBR                     |
| O-ring:                         | NBR                     |
| O-Ring:                         | NBR 70 SH               |
| Dichtungen:                     | Kunststoff              |
| Seals:                          | Plastics                |
| Rondella di tenuta sul filetto: | tecnopolimero           |
| zyl. Gewinde:                   | DIN EN ISO 228          |
| cyl. Threads:                   | DIN EN ISO 228          |
| Filettatura:                    | gas cilindrica ISO 228  |
| Betriebstemperatur:             | -20 °C bis +70 °C       |
| Working temperature:            | -20 °C up to +70 °C     |
| Temperatura di esercizio:       | da -20 °C a +70 °C      |
| Betriebsdruck:                  | max. 10 bar             |
| Working pressure:               | max. 10 bar             |
| Pressione di esercizio:         | max. 10 bar             |

Für geölte und ungeölte Druckluft.

For lubricated and non-lubricated compressed air.

Per aria compressa sia lubrificata che non.