


STX 029 Edelstahl

Drosselrückschlagventil mit Ringstück, Typ B, Abluft drosselbar

Unidirectional flow regulator type B for cylinders (stainless steel)

Regolatore di flusso unidirezionale per cilindro - Inox



ITV	ØD	G	H	L1 max	L2	sw
304814-ES	6	M5	3,7	24	21,5	8

Körper:	AISI 316L
Body:	AISI 316L
Corpo:	AISI 316L
O-Ring:	FKM
O-ring:	FKM
O-Ring:	FKM
Dichtungen:	FKM
Seals:	FKM
Rondella di tenuta sul filetto:	FKM
zyl. Gewinde:	DIN EN ISO 228
cyl. Threads:	DIN EN ISO 228
Filettatura:	gas cilindrica ISO 228
Betriebstemperatur:	-20 °C bis +150 °C
Working temperature:	-20 °C up to +150 °C
Temperatura di esercizio:	da -20 °C a +150 °C
Betriebsdruck:	-0,98 bis 16 bar
Working pressure:	-0,98 up to 16 bar
Pressione di esercizio:	da -0,98 a 16 bar
Für geölte und ungeölte Druckluft.	
For lubricated and non-lubricated compressed air.	
Per aria compressa sia lubrificata che non.	